


NO.	PIN NAME
1	LED A
2	LED K
3	LED K
4	VCI(2.8V)
5	IDVCC
6	RESET
7	TE
8	NC
9	GND
10	D0P
11	D0N
12	GND
13	D1P
14	D1N
15	GND
16	CLKP
17	CLKN
18	GND
19	D2P
20	D2N
21	GND
22	D3P
23	D3N
24	GND
25	NC
26	NC
27	NC
28	NC
29	NC
30	NC

LCD Type	3.44\"TFT, Transmissive Normally Black, IPS
Resolution	800(RGB)*800
View Direction	All O'CLOCK
LCD Driver IC	ILI9881C-05
Color Depth	16.7M
LCD Interface	4 MIPI
Operating voltage	2.8-3.3V
TP/Lens	Without
Backlight LEDs	8 LEDs, 40mA, 12.0V
Surface luminance	250 (typ)cd/m ²
Operating temperature	-20 °C ~ 70 °C
Storage temperature	-30 °C ~ 80 °C
Color chromaticity	[white] x/y:

NOTES:

1. GENERAL TOLERANCE: ± 0.2
2. () REFERENCE DIMENSION
3. Important dimension: ①~⑥

版本 (Version)	变更记录 (Revise History)	日期 (Date)	设计 (DESIGN)	Zahi
A0	Initial release	2023.06.20	审核 (CHECKED)	Aron
			批准 (APPROVED)	Aron
			客户承认 (CUSTOMER APPROVAL)	



TITLE: LCM	页面 (Page) 1 / 1
Drawing No. TST034HDBI-03	单位 (Unit) mm
	比例 (SCALE) 1 : 1
	角度 (Angle) ⊕